

# Technical Data Sheet

## WearMax Professional Shield

### Product No.: 6527

**General:** Waterborne Topcoat, based on Acrylic and Polyurethane Dispersions. WearMax Professional Shield

6527 dries clear and performs with excellent hardness, toughness, build, and stain resistance.

**Properties:** WearMax Professional Shield 6527 is specially developed to create superior stain and scratch

resistance. It guarantees excellent sunlight resistance as well as excellent flow. WearMax Professional Shield 6527 is VOC compliant and water soluble if not cured. WearMax Professional Shield 6527 levels perfectly, dries fast WearMax Professional Shield 6527 is available in 3 different gloss variations: Commercial

(Matte), Satin and Gloss.

- Spread rate: 900 – 1000 sq.ft. / Gal.
- Dry Time: 4 hrs.
- Viscosity: 17 – 18 sec. 4 mm DIN Cup
- Hazards: Health: 1 slight
- Fire: 0
- Reactivity: 1 slight
- Shelf Life: 12 Months in original unopened Container (stir properly before use)
- Appearance: Slightly milky opaque
- VOC: 90.3 gr/ltr.
- Solids: 30.2 %

#### Application:

- To be applied on WearMax Professional Armor 6525 only.
- Do not screen sealed surface.
- Mix with attached Catalyst and apply WearMax Professional Shield 6527 with a lightweight T-Bar and short nap applicator sleeve and roll with Truster Roller applicator immediately.
- Surface is ready to walk on after 12 hrs., wearing street shoes.
- WearMax Professional Shield 6527 is free of formaldehyde, insecticides/pesticides and heavy metals (according to EN 71).

**Remarks:** Truster Coatings is producing high quality coatings, based on suitable application methods and

technologies. Our proposal is considered as recommendation only without obligations. Our proposals are based on

experience and latest know-

how; they do not release from careful and proper production and quality control.

For further information see MSDS / Application instructions on label, or call Truster Coatings at 715.849.2989.

Revised 8.2.2006