

Technical Data Sheet

WearMax Professional Adhesion Primer

Product No.: 6507

General: Waterborne Base coat, based on Acrylic and Polyurethane Dispersions. WearMax Professional Adhesion Primer 6507 dries clear on all surfaces covered with Xtreme Finish, Vinyl, Rubber and Linoleum.

Properties: WearMax Professional Adhesion Primer 6507 is specially formulated to create a chemical bond on the non-porous substrates mentioned above. It guarantees superior sunlight resistance as well as excellent flow. WearMax Professional Adhesion Primer 6507 is VOC compliant and water soluble if not cured. WearMax Professional Adhesion Primer 6507 levels perfectly and dries fast. As WearMax Professional Adhesion Primer 6507 is applied on non-porous substrate additional sanding is not required. If contamination with dust or debris is noticed WearMax Professional Adhesion Primer 6507 can be buffed with floor buffer using a maroon pad.

- Spread rate: 1000 – 950 sq.ft. /Gal.
- Dry Time: 3 - 4 hrs.
- Viscosity: 14 – 15 sec. 4 mm DIN Cup
- Hazards: Health: 1 slight
- Fire: 0
- Reactivity: 1 slight
- Shelf Life: 12 Months in original unopened Container (stir vigorously before use)
- Appearance: milky white to slightly yellow
- VOC: 40.3 gr./ltr.
- Solids: 32.1 %

Application:

- If WearMax Professional Adhesion Primer 6507 is applied on Xtreme Wear Resistant finish, abrade floor with floor buffer and maroon pad.
- Vacuum and tack thoroughly.
- If applied on vinyl, VCT or linoleum strip substrate with stripper for PVC and rinse with plenty of clear water.
- Allow dry time of 3 – 4 hours.
- Apply 1 coat of WearMax Professional Primer 6507 with a lightweight T-Bar and short nap applicator sleeve and roll with Trustor Roller applicator immediately.
- Allow dry time of 3 – 4 hours.
- If necessary: Buff with maroon Pad.
- Apply WearMax Professional Armor and WearMax Professional Shield (see Technical Data Sheet).
- WearMax Professional Adhesion Primer 6507 is free of formaldehyde, insecticides/pesticides and heavy metals (according to EN 71).

Remarks: Trustor Coatings is producing high quality coatings, based on suitable application methods and technologies. Our proposal is considered as recommendation only without obligations. Our proposals are based on experience and latest know-how; they do not release from careful and proper production and quality control.

For further information see MSDS / Application instructions on label, or call Trustor Coatings at 715.849.2989.

Revised 8.2.2006