

# Technical Data Sheet

## WearMax Professional Armor

### Product No.: 6525

**General:** Waterborne Ceramic coat, based on Acrylic and Polyurethane Dispersions. WearMax Professional Armor 6524 dries clear and performs with excellent build.

**Properties:** WearMax Professional Armor is specially developed to create superior wear and scratch resistance. It guarantees superior sunlight resistance as well as excellent flow. WearMax Professional Armor 6525 is VOC compliant and water soluble if not cured. WearMax Professional Armor 6525 dries fast to a slightly textured surface, and appears deep matte. As Ceramics are very dense, sedimentation due to transportation might be observed. Therefore WearMax Professional Armor 6525 has to be stirred properly before and during use.

- Spread rate: 900 – 1000 sq.ft./Gal.
- Dry Time: 2 – 3 hrs.
- Viscosity: 28 – 30 sec. 4 mm DIN Cup
- Hazards: Health: 1 slight
  
- Fire: 0
  
- Reactivity: 1 slight
- Shelf Life: 12 Months in original unopened Container (stir properly before use)
- Appearance: milky white
- VOC: 107.6 gr/ltr.
- Solids: 48.7 %

#### Application:

- To be applied on WearMax Professional Adhesion Primer 6507 only. (See Technical Data Sheet)
- Allow drying time of 3–4 hours.
- Apply WearMax Professional Armor 6525 with a lightweight T-Bar and short nap applicator sleeve and roll with Truster Roller applicator immediately. Do not roll into dry or semi-dry areas. Keep a wet edge to avoid lap marks.
- Allow dry time of 2–3 hours.
- Do not buff.
- Apply desired WearMax Professional Shield 6527 (See Technical Data Sheet).
- WearMax Professional Armor 6524 is free of formaldehyde, insecticides/pesticides and heavy metals (according to EN 71).

**Remarks:** Truster Coatings is producing high quality coatings, based on suitable application methods and technologies. Our proposal is considered as recommendation only without obligations. Our proposals are based on experience and latest know-how; they do not release from careful and proper production and quality control.

For further information see MSDS / Application instructions on label, or call Truster Coatings at 715.849.2989.

Revised 8.2.2006