

Technical Data Sheet

WearMax Universal Sealer

Product No.: 6514

General: Waterborne Sealer, based on Acrylic and Polyurethane Dispersions, for old and sanded floors. WearMax Universal Sealer 6514 dries clear and performs with excellent build.

Properties: WearMax Universal Sealer is specially developed to create excellent adhesion on all wood species. It is formulated to guaranty excellent sunlight resistance as well as excellent flow. Universal Sealer 6514 is VOC compliant and water soluble if not cured. WearMax Universal Sealer 6514 levels perfectly and is easy to screen.

- Spread rate: 350 – 400 sq.ft./Gal.
- Dry Time: 2 – 3 hrs. to buff
- Viscosity: 17 – 19 sec. 4 mm DIN Cup
- Hazards: Health: 1 slight

- Fire: 0

- Reactivity: 1 slight
- Shelf Life: 12 Months in original unopened Container
- Appearance: Slightly milky opaque
- VOC: 54.0 gr./ltr.
- Solids: 33.6 %

Application:

- Prepare entire Floor according to NOFMA Standard
- Vacuum and tack with a damp towel.
- Apply WearMax Universal Sealer 6514 with a lightweight T-Bar and short nap applicator sleeve.
- Allow dry time of 2 – 3 hours. (check with moisture meter)
- Buff with 120 grit screen, or maroon pad with 180 – 240 grit sandpaper strips, vacuum and tack with damp towel.
- Apply desired Wearmax Armor/Top coat
- WearMax Universal Sealer 6514 is free of formaldehyde, insecticides/pesticides and heavy metals (according to EN 71).

Remarks: Trustor Coatings is producing high quality coatings, based on suitable application methods and technologies. Our proposal is considered as recommendation only without obligations. Our proposals are based on experience and latest know-how; they do not release from careful and proper production and quality control.

For further information see MSDS / Application instructions on label, or call Trustor Coatings at 715.849.2989.

Revised 8.2.2006